


FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9508925563781
SKU	FL.2712021.0002
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9503466743371
SKU	FL.3012021.0001
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9505695117398
SKU	FL.401201.0003
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9506654566837
SKU	FL.112021.0004
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9509155357515
SKU	FL.2712021.0010
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9506135333712
SKU	FL.3012021.0009
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9509191419178
SKU	FL.401201.0011
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9507544667863
SKU	FL.112021.0012
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9506754534750
SKU	FL.2712021.0014
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9507413712922
SKU	FL.3012021.0013
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS




EAN	9509294416159
SKU	FL.401201.0015
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE ROUND



DIMENSIONS



EAN	9503955984315
SKU	FL.112021.0016
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

