


FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9501537763631
SKU	FL.2712021.0018
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9509846865985
SKU	FL.3012021.0017
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9505882134719
SKU	FL.401201.0019
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9508382215476
SKU	FL.112021.0020
Energy rating	-
Collection	FLEXX
Colour	Black
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9504458434215
SKU	FL.2712021.0022
Energy rating	-
Collection	FLEXX
Colour	Gold
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9508814216576
SKU	FL.3012021.0021
Energy rating	-
Collection	FLEXX
Colour	Gold
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9509729159453
SKU	FL.401201.0023
Energy rating	-
Collection	FLEXX
Colour	Gold
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9507763486320
SKU	FL.112021.0024
Energy rating	-
Collection	FLEXX
Colour	Gold
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9502758643351
SKU	FL.2712021.0026
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9503185698815
SKU	FL.3012021.0025
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9501371499482
SKU	FL.401201.0027
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9506382969382
SKU	FL.112021.0028
Energy rating	-
Collection	FLEXX
Colour	Rvs
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9502287113646
SKU	FL.2712021.0030
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9503544368793
SKU	FL.3012021.0029
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS




EAN	9505685122593
SKU	FL.401201.0031
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	-
Lumen	-
Colour temperature	4000K
Colour Rendering Index	CRI>90
Efficacy	-
Lifetime	>50.000h
Beam angle	-
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



FLEXX CEILING SPOT TILTABLE SQUARE



DIMENSIONS



EAN	9502618978999
SKU	FL.112021.0032
Energy rating	-
Collection	FLEXX
Colour	White
IP rating	IP20
Light source	LED
Power	5.5 W
Lumen	500 Lm
Colour temperature	DIM TO WARM
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	95 x 100 x 70 mm
Product dimensions	-
Package weight	210 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

