


HALO 3-RING Ø920



DIMENSIONS




EAN	9508781568142
SKU	HA.302021.0026
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9504987978884
SKU	HA.3012021.0027
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9506361433156
SKU	HA.3022021.0028
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9502845752188
SKU	HA.3052021.0110
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9505957914772
SKU	HA.302021.0038
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9509232542919
SKU	HA.3012021.0039
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS




EAN	9509224241455
SKU	HA.3022021.0040
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO 3-RING Ø920



DIMENSIONS



EAN	9504436539239
SKU	HA.3052021.0119
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	111 W
Lumen	10121 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	6219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

