


HALO INWARD Ø660



DIMENSIONS




EAN	9508578329567
SKU	HA.302021.0010
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	700 x 700 x 90 mm
Product dimensions	700 x 700 x 90 mm
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9507272758666
SKU	HA.3012021.0092
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	700 x 700 x 90 mm
Product dimensions	Ø660
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9501467622961
SKU	HA.3022021.0093
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	700 x 700 x 90 mm
Product dimensions	Ø660
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9506248762317
SKU	HA.3052021.0107
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	700 x 700 x 90 mm
Product dimensions	Ø660
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9505883429890
SKU	HA.302021.0011
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	700 x 700 x 90 mm
Product dimensions	700 x 700 x 90 mm
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9504559121533
SKU	HA.3012021.0012
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	700 x 700 x 90 mm
Product dimensions	700 x 700 x 90 mm
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS




EAN	9506733158649
SKU	HA.3022021.0013
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	700 x 700 x 90 mm
Product dimensions	700 x 700 x 90 mm
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø660



DIMENSIONS



EAN	9502675886855
SKU	HA.3052021.0113
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	31 W
Lumen	2818 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	90.9 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	700 x 700 x 90 mm
Product dimensions	Ø660
Package weight	1930 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

