


HALO INWARD Ø790



DIMENSIONS




EAN	9503969482883
SKU	HA.302021.0029
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9504265673685
SKU	HA.3012021.0030
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9507941292354
SKU	HA.3022021.0031
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9506641495843
SKU	HA.3052021.0108
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9509317931782
SKU	HA.302021.0032
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9508391318380
SKU	HA.3012021.0033
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS




EAN	9504916129899
SKU	HA.3022021.0034
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø790



DIMENSIONS



EAN	9506163347279
SKU	HA.3052021.0117
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	37 W
Lumen	3374 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.2 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	830 x 830 x 90 mm
Product dimensions	Ø790
Package weight	2470 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

