


HALO INWARD Ø920



DIMENSIONS




EAN	9504389697123
SKU	HA.302021.0017
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9502731631368
SKU	HA.3012021.0018
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9503693929784
SKU	HA.3022021.0019
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9507988917913
SKU	HA.3052021.0109
Energy rating	-
Collection	HALO
Colour	Black
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9505414139984
SKU	HA.302021.0020
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	-
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9504969786827
SKU	HA.3012021.0021
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS




EAN	9502552622798
SKU	HA.3022021.0022
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



HALO INWARD Ø920



DIMENSIONS



EAN	9503851223129
SKU	HA.3052021.0116
Energy rating	-
Collection	HALO
Colour	White
IP rating	IP20
Light source	LED
Power	43 W
Lumen	3929 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	91.4 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	960 x 960 x 90 mm
Product dimensions	Ø920
Package weight	3219 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

