



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743267254
SKU	LI.2712021.0320
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743299231
SKU	LI.2722021.0321
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743424466
SKU	LI.2752021.0322
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743432447
SKU	LI.2742021.0323
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743185176
SKU	LI.3012021.0316
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743198138
SKU	LI.3022021.0317
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743216252
SKU	LI.3052021.0318
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150743244262
SKU	LI.3042021.0319
Energy rating	-
Collection	LINE
Colour	Black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150736063016
SKU	LI.2712021.0160
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150736063047
SKU	LI.2722021.0161
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150736086008
SKU	LI.2752021.0162
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150736149147
SKU	LI.2742021.0163
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9508999768129
SKU	LI.3012021.0156
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9508739241936
SKU	LI.3022021.0157
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735891887
SKU	LI.3052021.0158
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735994991
SKU	LI.3042021.0159
Energy rating	-
Collection	LINE
Colour	Brushed black
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734313373
SKU	LI.2712021.0096
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734336303
SKU	LI.2722021.0097
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734347354
SKU	LI.2752021.0098
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734375319
SKU	LI.2742021.0099
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9508183499143
SKU	LI.3012021.0092
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9509463578770
SKU	LI.3022021.0093
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734035039
SKU	LI.3052021.0094
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150734186137
SKU	LI.3042021.0095
Energy rating	-
Collection	LINE
Colour	Brushed bronze
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735048076
SKU	LI.2712021.0128
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735056040
SKU	LI.2722021.0129
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735064076
SKU	LI.2752021.0130
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735081073
SKU	LI.2742021.0131
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9503991346955
SKU	LI.3012021.0124
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9501842966413
SKU	LI.3022021.0125
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735038022
SKU	LI.3052021.0126
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150735048045
SKU	LI.3042021.0127
Energy rating	-
Collection	LINE
Colour	Brushed champagne
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150733018064
SKU	LI.2712021.0032
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150733038048
SKU	LI.2722021.0033
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150733038093
SKU	LI.2752021.0034
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150733071038
SKU	LI.2742021.0035
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	2700K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9502217974392
SKU	LI.3012021.0028
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Triac
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	9509166894580
SKU	LI.3022021.0029
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Dali
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM




DIMENSIONS




EAN	6150732960975
SKU	LI.3052021.0030
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Zigbee
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years



LINE UP-DOWN 2500MM



DIMENSIONS



EAN	6150732983981
SKU	LI.3042021.0031
Energy rating	-
Collection	LINE
Colour	Brushed gold
IP rating	IP20
Light source	LED
Power	75 W
Lumen	8500 Lm
Colour temperature	3000K
Colour Rendering Index	CRI>90
Efficacy	113.3 Lm/W
Lifetime	>50.000h
Beam angle	Diffuse
Driver	Yes
Voltage	24 V
Input voltage	220-240 V
Dim	Casambi
Package dimensions	1000 - 2500 x 25 x 45 mm
Product dimensions	2500 x 25 x 45 mm
Package weight	3345 g
HS code	94054990
ETL code	-
Material	Aluminium
Warranty	2 years

