


**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 2700K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9503326388957
<b>SKU</b>	S40.27120361.0003
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed black
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years




**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 2700K

**A**  
**B**  
**C**  
**D**  
**E** ←  
**F**  
**G**

**5**  
 kWh/1000h

 2019/2015


<b>EAN</b>	9502547811343
<b>SKU</b>	S40.27220361.0004
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed black
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years




**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 3000K

**A**  
**B**  
**C**  
**D**  
**E**  
**F**  
**G**

**5**  
 kWh/1000h

 2019/2015


<b>EAN</b>	9503749995855
<b>SKU</b>	S40.30120361.0001
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed black
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years




**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 3000K

**A**  
**B**  
**C**  
**D**  
**E** ←  
**F**  
**G**

**5**  
 kWh/1000h

 2019/2015


<b>EAN</b>	9501731682899
<b>SKU</b>	S40.30220361.0002
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed black
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 2700K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9508842857512
<b>SKU</b>	S40.27120361.0015
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed bronze
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years




**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 2700K

**A**  
**B**  
**C**  
**D**  
**E** ←  
**F**  
**G**

**5**  
 kWh/1000h

 2019/2015


<b>EAN</b>	9504257184977
<b>SKU</b>	S40.27220361.0016
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed bronze
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 3000K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9506754998750
<b>SKU</b>	S40.30120361.0013
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed bronze
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 3000K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015

<b>EAN</b>	9508942636338
<b>SKU</b>	S40.30220361.0014
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed bronze
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years







**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 2700K

A  
 B  
 C  
 D  
**E**  
 F  
 G

**5**  
 kWh/1000h

 2019/2015


<b>EAN</b>	9505944793816
<b>SKU</b>	S40.27120361.0007
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed champagne
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 2700K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9509211633874
<b>SKU</b>	S40.27220361.0008
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed champagne
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 3000K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9504513636561
<b>SKU</b>	S40.30120361.0005
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed champagne
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 3000K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9506719983197
<b>SKU</b>	S40.30220361.0006
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed champagne
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 2700K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9508789679123
<b>SKU</b>	S40.27120361.0011
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed gold
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 2700K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9506483745847
<b>SKU</b>	S40.27220361.0012
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed gold
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	2700K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years



**SPOT40 SURFACE**



**DIMENSIONS**



**ENERGY**

Lightinova  
SPOT40 surface mounted LED 3000K

A  
B  
C  
D  
E  
F  
G

**E**

**5**  
kWh/1000h

2019/2015


<b>EAN</b>	9503541792621
<b>SKU</b>	S40.30120361.0009
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed gold
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Triac
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years




**SPOT40 SURFACE**




**DIMENSIONS**



  
**Lightinova**  
 SPOT40 surface mounted LED 3000K

**A**  
**B**  
**C**  
**D**  
**E** ←  
**F**  
**G**

**5**  
 kWh/1000h

 2019/2015

<b>EAN</b>	9504817718598
<b>SKU</b>	S40.30220361.0010
<b>Energy rating</b>	E
<b>Collection</b>	SPOT40
<b>Colour</b>	Brushed gold
<b>IP rating</b>	IP20
<b>Light source</b>	LED
<b>Power</b>	4.5 W
<b>Lumen</b>	540 Lm
<b>Colour temperature</b>	3000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	120 Lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	36 D
<b>Driver</b>	Yes
<b>Voltage</b>	24 V
<b>Input voltage</b>	220-240 V
<b>Dim</b>	Dali
<b>Package dimensions</b>	220 x 105 x 105 mm
<b>Product dimensions</b>	ø40 x 95 mm
<b>Package weight</b>	550 g
<b>HS code</b>	94054990
<b>ETL code</b>	-
<b>Material</b>	Aluminium
<b>Warranty</b>	2 years

